



Innovation meets Simplicity: Intelligent lighting revolutionises HighBay illumination

GreenUp Highbay G2

Height is not an issue any more, maximum 16 m movement detection together with the wireless ZigBee control, GreenUp HighBay G2, light up your space smartly.

Benefits

- Light as need, provides additional energy savings on the intelligent version (BY560X) (depends on usage behaviour)
- Future-proof system: wireless adjustment of lighting settings and fast re-zoning if use of space changes via the intelligent version (BY560X)
- Precise light distribution to light up your space efficiently
- Provides better protection against dust and insects

Features

- Different lighting levels and timings can be set per sensor, group and ZigBee network of luminaires (BY560X)
- Advanced sensor technology for effective presence and daylight detection
- High efficacy: Up to 140 lumens per watt
- CRI>80; R9>0; Wide beam, narrow beam and high rack optic choices are available
- Lifetime 65 Khrs @L70B50 with IP40 protection

Application

- General Industry Application: Warehouse; Distribution centre; Factory
- Indoor sports hall
- Other high ceiling indoor applications

GreenUp Highbay G2

Warnings and Safety

- The product is IPX0 & as such is not protected against water ingress and as such we strongly recommend that the environment in which the luminaire is to be installed is suitably checked
- If the above advice is not taken and the luminaires are subject to water ingress, Philips/Signify cannot guarantee safe failure and product warranty will become void


Versions



Product details



GreenUp Highbay G2 BY560P
LED105 B




GreenUp Highbay G2 BY560P
LED105 F



GreenUp Highbay G2 BY560P
LED210 B



GreenUp Highbay G2 BY560P
LED210 F



GreenUp Highbay G2 BY560P
LED160 F



GreenUp Highbay G2 BY560P
LED160 B

GreenUp Highbay G2

-	
Driver failure rate at 5,000 hours	0.01 %
Application Conditions	
Ambient temperature range	-20 to +45 °C
Suitable for random switching	No
Approval and Application	
Mech. impact protection code	IK03
Ingress protection code	IP40
Operating and Electrical	
Input Voltage	220 to 240 V
General Information	
Beam angle of light source	- °
CE mark	CE mark
Protection class IEC	Safety class I (I)
Optical cover/lens type	LIN-PC
Driver included	Yes
ENEC mark	-
Flammability mark	F
Glow-wire test	650/5
Light source replaceable	No
Number of gear units	1 unit
Initial Performance (IEC Compliant)	
Initial chromaticity	(0.38.0.38)SDCM<5
Init. Corr. Colour Temperature	4000 K
Init. Colour rendering index	>80
Luminous flux tolerance	+/-10%
Mechanical and Housing	
Colour	Aluminum and white
Over Time Performance (IEC Compliant)	
Median useful life L80B50	45000 h
Median useful life L90B50	25000 h

Application Conditions

Order Code	Full Product Name	Maximum dimming level
01502351	BY560P LED210/NW PSU WB	Not applicable
01502451	BY560P LED210/NW PSU NB	Not applicable
01502751	BY560P LED210/NW PSU HRO	Not applicable
01507551	BY560P LED210/NW PSD/CL WB	1% (depends on dimmer, ELV)
01507751	BY560P LED210/NW PSD/CL HRO	1% (depends on dimmer, ELV)
01507851	BY560P LED210/NW PSD/CL NB	1% (depends on dimmer, ELV)
01502651	BY560P LED105/NW PSD/CL HRO	1% (depends on dimmer, ELV)
01502951	BY560P LED105/NW PSU WB	Not applicable
01503051	BY560P LED105/NW PSU HRO	Not applicable
01504251	BY560P LED105/NW PSU NB	Not applicable
01507051	BY560P LED105/NW PSD/CL WB	1% (depends on dimmer, ELV)
01507151	BY560P LED105/NW PSD/CL NB	1% (depends on dimmer, ELV)
01503551	BY560P LED160/NW PSU HRO	Not applicable
01503951	BY560P LED160/NW PSU NB	Not applicable
01504051	BY560P LED160/NW PSU WB	Not applicable
01506851	BY560P LED160/NW PSD/CL HRO	1% (depends on dimmer, ELV)
01507351	BY560P LED160/NW PSD/CL NB	1% (depends on dimmer, ELV)
01507451	BY560P LED160/NW PSD/CL WB	1% (depends on dimmer, ELV)

Controls and Dimming

Order Code	Full Product Name	Dimmable	Order Code	Full Product Name	Dimmable
01502351	BY560P LED210/NW PSU WB	No	01504251	BY560P LED105/NW PSU NB	No
01502451	BY560P LED210/NW PSU NB	No	01507051	BY560P LED105/NW PSD/CL WB	Yes
01502751	BY560P LED210/NW PSU HRO	No	01507151	BY560P LED105/NW PSD/CL NB	Yes
01507551	BY560P LED210/NW PSD/CL WB	Yes	01503551	BY560P LED160/NW PSU HRO	No
01507751	BY560P LED210/NW PSD/CL HRO	Yes	01503951	BY560P LED160/NW PSU NB	No
01507851	BY560P LED210/NW PSD/CL NB	Yes	01504051	BY560P LED160/NW PSU WB	No
01502651	BY560P LED105/NW PSD/CL HRO	Yes	01506851	BY560P LED160/NW PSD/CL HRO	Yes
01502951	BY560P LED105/NW PSU WB	No	01507351	BY560P LED160/NW PSD/CL NB	Yes
01503051	BY560P LED105/NW PSU HRO	No	01507451	BY560P LED160/NW PSD/CL WB	Yes

GreenUp Highbay G2

General Information

Order Code	Full Product Name	Optic type
01502351	BY560P LED210/NW PSU WB	WB
01502451	BY560P LED210/NW PSU NB	NB
01502751	BY560P LED210/NW PSU HRO	HRO
01507551	BY560P LED210/NW PSD/CL WB	WB
01507751	BY560P LED210/NW PSD/CL HRO	HRO
01507851	BY560P LED210/NW PSD/CL NB	NB
01502651	BY560P LED105/NW PSD/CL HRO	HRO
01502951	BY560P LED105/NW PSU WB	WB
01503051	BY560P LED105/NW PSU HRO	HRO

Order Code	Full Product Name	Optic type
01504251	BY560P LED105/NW PSU NB	NB
01507051	BY560P LED105/NW PSD/CL WB	WB
01507151	BY560P LED105/NW PSD/CL NB	NB
01503551	BY560P LED160/NW PSU HRO	HRO
01503951	BY560P LED160/NW PSU NB	NB
01504051	BY560P LED160/NW PSU WB	WB
01506851	BY560P LED160/NW PSD/CL HRO	HRO
01507351	BY560P LED160/NW PSD/CL NB	NB
01507451	BY560P LED160/NW PSD/CL WB	WB

Initial Performance (IEC Compliant)

Order Code	Full Product Name	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
01502351	BY560P LED210/NW PSU WB	137 lm/W	21000 lm	153 W
01502451	BY560P LED210/NW PSU NB	137 lm/W	21000 lm	153 W
01502751	BY560P LED210/NW PSU HRO	137 lm/W	21000 lm	153 W
01507551	BY560P LED210/NW PSD/CL WB	137 lm/W	21000 lm	153 W
01507751	BY560P LED210/NW PSD/CL HRO	137 lm/W	21000 lm	153 W
01507851	BY560P LED210/NW PSD/CL NB	137 lm/W	21000 lm	153 W
01502651	BY560P LED105/NW PSD/CL HRO	140 lm/W	10500 lm	75 W
01502951	BY560P LED105/NW PSU WB	140 lm/W	10500 lm	75 W
01503051	BY560P LED105/NW PSU HRO	140 lm/W	10500 lm	75 W

Order Code	Full Product Name	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
01504251	BY560P LED105/NW PSU NB	140 lm/W	10500 lm	75 W
01507051	BY560P LED105/NW PSD/CL WB	140 lm/W	10500 lm	75 W
01507151	BY560P LED105/NW PSD/CL NB	140 lm/W	10500 lm	75 W
01503551	BY560P LED160/NW PSU HRO	133 lm/W	16000 lm	120 W
01503951	BY560P LED160/NW PSU NB	133 lm/W	16000 lm	120 W
01504051	BY560P LED160/NW PSU WB	133 lm/W	16000 lm	120 W
01506851	BY560P LED160/NW PSD/CL HRO	133 lm/W	16000 lm	120 W
01507351	BY560P LED160/NW PSD/CL NB	133 lm/W	16000 lm	120 W
01507451	BY560P LED160/NW PSD/CL WB	133 lm/W	16000 lm	120 W

