



The new generation of energy-saving LED PLC 4P tube lighting

CorePro LED PLC 4P

The CorePro LED PLC 4P integrates a LED light source into a traditional fluorescent form factor. This product is the ideal solution for uplampping in general lighting applications: it meets basic lighting requirements, offers significant energy savings and is environmentally friendly.

Benefits

- Reduced operational cost thanks to lower energy consumption
- Lower maintenance cost thanks to 2-3 times longer lifetime than conventional lamps
- The fastest and easiest way to upgrade existing luminaires to LED technology
- Completely safe product and installation process

Features

- Highly energy-efficient
- Easy installation
- Conventional form factor to fit into existing luminaires
- No mercury

Application

- Hospitality, retail, office, industrial and home applications

CorePro LED PLC 4P

Versions





8.5W G24q-3 4P



6.5W G24q-2 4P

Dimensional drawing



Product	D1	D2	A1	A2	A3
CorePro LED PLC 6.5W 840 4P G24q-2	24.3 mm	28.4 mm	105.8 mm	125 mm	140.6 mm
CorePro LED PLC 6.5W 830 4P G24q-2	24.3 mm	28.4 mm	105.8 mm	125 mm	140.6 mm

Product	D1	D2	A1	A2	A3
CorePro LED PLC 9W 840 4P G24q-3	24.3 mm	28.4 mm	128.8 mm	148 mm	163.6 mm
CorePro LED PLC 9W 830 4P G24q-3	24.3 mm	28.4 mm	128.8 mm	148 mm	163.6 mm

CorePro LED PLC 4P

Controls and Dimming

Dimmable	No
----------	----

Operating and Electrical

Input Frequency	30000-80000 Hz
Voltage (Nom)	20-50 V
Starting Time (Nom)	0.5 s

General Information

Nominal Lifetime (Nom)	30000 h
Switching Cycle	50,000X

Light Technical

Beam Angle (Nom)	120 °
Colour Rendering Index (Nom)	83
Llmf At End Of Nominal Lifetime (Nom)	70 %

Mechanical and Housing

Bulb Shape	Tube, single-ended
------------	--------------------

Temperature

T-Ambient (Max)	35 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	65 °C
T-Storage (Min)	-40 °C

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/1000 h
54115900	CorePro LED PLC 9W 830 4P G24q-3	9 kWh
54117300	CorePro LED PLC 9W 840 4P G24q-3	9 kWh
54119700	CorePro LED PLC 6.5W 830 4P G24q-2	7 kWh
54121000	CorePro LED PLC 6.5W 840 4P G24q-2	7 kWh

Operating and Electrical

Order Code	Full Product Name	Power (Nom)
54115900	CorePro LED PLC 9W 830 4P G24q-3	9 W
54117300	CorePro LED PLC 9W 840 4P G24q-3	9 W

Order Code	Full Product Name	Power (Nom)
54119700	CorePro LED PLC 6.5W 830 4P G24q-2	6.5 W
54121000	CorePro LED PLC 6.5W 840 4P G24q-2	6.5 W

General Information

Order Code	Full Product Name	Cap-Base
54115900	CorePro LED PLC 9W 830 4P G24q-3	G24Q-3
54117300	CorePro LED PLC 9W 840 4P G24q-3	G24Q-3

Order Code	Full Product Name	Cap-Base
54119700	CorePro LED PLC 6.5W 830 4P G24q-2	G24Q-2
54121000	CorePro LED PLC 6.5W 840 4P G24q-2	G24Q-2

Light Technical

Order Code	Full Product Name	Colour Code	Correlated Colour	
			Temperature (Nom)	Luminous Flux (Nom)
54115900	CorePro LED PLC 9W 830 4P G24q-3	830	3000 K	950 lm
54117300	CorePro LED PLC 9W 840 4P G24q-3	841	4000 K	1000 lm

Order Code	Full Product Name	Colour Code	Correlated Colour	
			Temperature (Nom)	Luminous Flux (Nom)
54119700	CorePro LED PLC 6.5W 830 4P G24q-2	830	3000 K	650 lm
54121000	CorePro LED PLC 6.5W 840 4P G24q-2	841	4000 K	700 lm

Temperature

CorePro LED PLC 4P

Order Code	Full Product Name	T-Case Maximum (Nom)
54115900	CorePro LED PLC 9W 830 4P G24q-3	76 °C
54117300	CorePro LED PLC 9W 840 4P G24q-3	76 °C
54119700	CorePro LED PLC 6.5W 830 4P G24q-2	66 °C
54121000	CorePro LED PLC 6.5W 840 4P G24q-2	66 °C

