



# Electronic ignitor for HID lamp circuits

## SN 58

HID ignitors for semi-parallel systems


### Product data

General Information	
Application code	58
Operating and Electrical	
Input Voltage	220 to 240 V
Input frequency	50 to 60 Hz
Ignition type	Semi-Parallel
Ignition voltage (max.)	5.0 kV
Ignition voltage (min.)	2.8 kV
Response voltage	190 V
Mains voltage performance (AC)	-8%+6%
Mains voltage safety (AC)	-10%+10%
Power losses (nom.)	0.2 W
Wiring	
Ballast contact wire cross section	0.50-2.50 mm <sup>2</sup>
Connector type	Screw
Temperature	
T-ambient (max.)	85 °C

T-ambient (min.)	-20 °C
T-Case maximum (max.)	90 °C
Mechanical and Housing	
Housing	Akulon S223
Approval and Application	
Approval marks	CE marking ENEC certificate
Product Data	
Full product code	697013372881900
Order product name	SN 58
EAN/UPC – product	6970133728819
Order code	72881900
SAP numerator – quantity per pack	1
Numerator – packs per outer box	48
SAP material	913710010513
SAP net weight (piece)	0.049 kg

## Electronic ignitor for HID lamp circuits

### Dimensional drawing



Product	C1	A1	A2	B1
SN 58	38.5 mm	85.5 mm	65.0 mm	41.5 mm

SN 58

