



# A flexible and affordable all-rounder for retail applications

## GreenSpace Accent Projector

Thanks to the GreenSpace Accent family of projectors, retailers and building operators can enjoy the superior quality of light and market-leading energy efficiency of PerfectAccent optics for a reasonable initial investment. The new PerfectAccent optics provide high-quality light that adds sparkle to merchandise at the same time as enhancing the shoppers' eye comfort. Installation and repositioning are both quick and easy and require no additional tools as GreenSpace Accent Projectors integrate seamlessly onto 3C- and DALI-tracks, CoreLine Trunking and Maxos fusion. For fashion (shops) and food retailers (supermarkets, hyperstores), the GreenSpace Accent Projector is available with special LED flavours and fresh food LED lighting recipes to show the merchandise in the very best light. Check out our Fashion and Food catalogue pages to find out more about PremiumWhite, PremiumColour, Fresh Meat, Rosé, Frost and Champagne.

### Benefits

- Blends into stores with a clean, robust and neutral design
- Increased sparkle and shopper eye comfort with PerfectAccent optics
- High energy-efficiency, maintained over the full lifetime of the product

### Features

- Tool-less installation and repositioning on Track (ST321T), CoreLine Trunking (ST321Y; a double spotlight version) or Maxos fusion (ST321S)
- Available with a high flux up to 4,900 lm, a wide range of optics, optional front glass and barndoor accessories
- Retail LED flavours and fresh food LED lighting recipes included
- Very broad aiming flexibility, including upward lighting
- Available for normal mains (PSU), simple DALI dimming (PSD), Interact compatible DALI (DIA) and indoor positioning (DIA-VLC)

# GreenSpace Accent Projector

## Application

- Convenience stores
- Supermarkets and hypermarkets
- Fashion stores

## Warnings and Safety

- All photometrical data is calculated without optional front glass. Flux should be reduced by 3.5% when using a front glass
- Cleaning of the optic is only allowed if pressurised air is used. Touching the LED or reflector is forbidden. For food preparation areas and areas with high levels of dust, the use of the optional front glass is strongly advised, as it can be cleaned with a (dry) microfibre cloth.
- During maintenance, the product must be switched off and cooled down
- The product must be installed out of arm's reach. Manipulating the product when hot is only possible with an insulated glove

## Versions

GREENSPACE ACCENT MAXOS  
FUSION GEN2 - 24°



## Product details



ST321T - GreenSpace Accent  
Projector back view white



ST321T - GreenSpace Accent  
Projector RPO plastic white



ST321Y - GreenSpace Accent  
Projector Coreline trunking  
connect

# GreenSpace Accent Projector

## Application Conditions

Ambient temperature range	+10 to +40 °C
Maximum dimming level	Not applicable
Suitable for random switching	Not applicable

## Approval and Application

Mech. impact protection code	IK02
Ingress protection code	IP20

## Controls and Dimming

Dimmable	No
----------	----

## Operating and Electrical

Input Voltage	220 to 240 V
---------------	--------------

## General Information

Beam angle of light source	120 °
CE mark	CE mark
Protection class IEC	Safety class II (II)
Driver included	Yes
ENEC mark	ENEC mark
Flammability mark	NO
Glow-wire test	650/30
Light source replaceable	No
Number of gear units	2 units
Optic type	WB
Product family code	ST321Y

## Initial Performance (IEC Compliant)

Initial chromaticity	(0.38, 0.38) SDCM<3
Init. Corr. Colour Temperature	4000 K
Init. Colour rendering index	≥80
Luminous flux tolerance	+/-10%

## Mechanical and Housing

Colour	White
--------	-------

## Initial Performance (IEC Compliant)

Order Code	Full Product Name	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
97496100	ST321Y LED27S/840 PSU WB WH	115 lm/W	2700 lm	23.5 W
97499200	ST321Y LED39S/840 PSU WB WH	139 lm/W	3900 lm	28 W

