



HF-Performer III for TL5 lamps

HF-P 1 14-35 TL5 HE III 220-240V

HF-Performer III TL5 ballasts offer maximum versatility and meet all of the necessary commercial grade specifications. They also offer the added benefits of lamp striation reduction technology, making these ballasts compatible with energy-saving TL5 ECO lamps. As such, these ballasts are part of an overall high-efficiency lighting system that may help you or your customers to achieve any international or local energy code you need to comply with. HF-Performer III TL5 ballasts are the ideal choice for a broad range of new construction and retrofit applications within the commercial sector, including general surface mounting or office lighting, parking garages, warehouses, waterproof and other applications. The ballast is primarily designed for Indoor application. For outdoor application, the luminaire should be minimum Classland need to be sufficiently protected against water & dust. The installation should also be guard against any lightening surge or any other necessary electrical protection as deemed in such typical installation & application.

Product data

| Operating and Electrical | | Wiring | |
|----------------------------------------------|--------------|---------------------------------|---------------------------------------------------------------------------------------------------|
| Line Frequency | 50 to 60 Hz | Connector Type Input Terminals | WAGO 251 universal connector [Suitable for both automatic wiring (ALF and ADS) and manual wiring] |
| Input Frequency | 50 to 60 Hz | Connector Type Output Terminals | WAGO 251 universal connector [Suitable for both automatic wiring (ALF and ADS) and manual wiring] |
| Input Voltage | 220 to 240 V | | |
| Inrush Current Width | 0.25 ms | | |
| Inrush Current Peak (Max) | 24 A | | |
| Number of Products on MCB (16A Type B) (Nom) | 28 | | |
| | | Temperature | |
| | | Ambient temperature range | -25 °C to 60 °C |
| | | T-Case Lifetime (Nom) | 80 °C |

HF-Performer III for TL5 lamps

| | |
|---------------------------------|-------------------------------------------------|
| T-Case Maximum (Max) | 80 °C |
| Mechanical and Housing | |
| Housing | L360x30x22 |
| Approval and Application | |
| Ingress protection code | IP20 [Finger-protected] |
| Energy Efficiency Index | A2 BAT |
| Safety Standard | IEC 61347-2-3 |
| Environmental Standard | ISO 14001 |
| Approval Marks | CE marking ENEC certificate VDE-EMV certificate |

| | |
|---------------------------------|----------------------------------|
| Product Data | |
| Full product code | 872790090504500 |
| Order product name | HF-P 1 14-35 TL5 HE III 220-240V |
| Order code | 913713031066 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 12 |
| Material Nr. (12NC) | 913713031066 |
| Full product name | HF-P 1 14-35 TL5 HE III 220-240V |
| EAN/UPC - Case | 8727900905045 |

Dimensional drawing

A2

| Product | D1 | C1 | A1 | A2 | B1 |
|----------------------------------|--------|---------|----------|----------|---------|
| HF-P 1 14-35 TL5 HE III 220-240V | 4.2 mm | 22.0 mm | 360.0 mm | 350.0 mm | 30.0 mm |

