



MASTERColour CDM-R

MASTERC CDM-R 35W/830 E27 PAR30L 30D 1CT

Range of compact, high-efficiency, discharge reflector lamps with a stable color over lifetime and a crisp, sparkling light

Warnings and Safety

- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Use only with electronic control gear. Color 830 lamps may also use electromagnetic gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

| General Information | | Luminous Flux in 90° Cone (Rated) | |
|---------------------------------------|----------------------------------|-----------------------------------|----------------------------------|
| Cap-Base | E27 [E27] | 2,000 lumen | |
| Operating Position | UNIVERSAL [Any or Universal (U)] | Operating and Electrical | |
| Switching Cycle | 1,000 | Power Consumption | 39.1 W |
| Life to 50% Failures (Nom) | 8,000 hour(s) | Warm-up time to 60% light | 120 s |
| Light Technical | | Voltage (Nom) | 86 V |
| Color Code | 830 [CCT of 3000K] | Voltage (Nom) | 86 V |
| Beam Angle (Nom) | 30 degree(s) | Controls and Dimming | |
| Luminous Intensity (Nom) | 7,400 cd | Dimmable | No |
| Color Designation | Warm White (WW) | Mechanical and Housing | |
| Chromaticity Coordinate X (Nom) | 0.431 | Bulb Finish | Clear |
| Chromaticity Coordinate Y (Nom) | 0.400 | Bulb Shape | PAR30L [PAR 3.75 inch/95mm Long] |
| Correlated Color Temperature (Nom) | 3000 K | | |
| Color rendering index (CRI) | 81 | | |
| LLMF At End Of Nominal Lifetime (Nom) | 48 % | | |

MASTERC colour CDM-R

Approval and Application


| | |
|-------------------------------|--------|
| Mercury (Hg) Content (Nom) | 2.8 mg |
| Energy Consumption kWh/1000 h | 42 kWh |

Product Data

| | |
|--------------------|--|
| Full product code | 871150021170500 |
| Order product name | MASTERC CDM-R 35W/830 E27 PAR30L 30D 1CT |
| Order code | 928071000691 |

| | |
|---------------------------------|--|
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 6 |
| Material Nr. (12NC) | 928071000691 |
| Full product name | MASTERC CDM-R 35W/830 E27 PAR30L 30D 1CT |
| EAN/UPC - Case | 8711500211712 |
| EAN/UPC - Product/Case | 8711500211705 |

Dimensional drawing



| Product | D (max) | D | C (max) | C |
|--|---------|-------|---------|--------|
| MASTERC CDM-R 35W/830 E27 PAR30L 30D 1CT | 97 mm | 95 mm | 123 mm | 120 mm |

Photometric data

170° / 180° / 150°




Light Distribution Diagram - MASTERC CDM-R 35W/830 E27 PAR30L 30D 1CT

Spectral Power Distribution Colour - MASTERC CDM-R 35W/830 E27 PAR30L 30D 1CT

MASTERC colour CDM-R

Lifetime



Life Expectancy Diagram - MASTERC CDM-R 35W/830 E27 PAR30L 30D 1CT

Lumen Maintenance Diagram - MASTERC CDM-R 35W/830 E27 PAR30L 30D 1CT

