



# Product Description

## Gear for SDW-T lamps

CSLS electronic control unit with impregnated (HID 'BASIC' ) or encapsulated (HID 'Heavy Duty' ) electromagnetic ballasts

### Benefits

- Electronic control unit ensures reliable starting and stabilizes lamp power for optimum performance (minimum color deviation)
- Simple installation and cabling

### Features

- Ballasts and electronic control units equipped with screw terminal blocks; other contact possibilities for
- Earthing-while-mounting facility (HID 'BASIC' ballasts), separate earth terminal (HID 'Heavy Duty' )

### Application



- Similar to those of the related lamps

### Warnings and Safety

- Climatic suitability CSLS and HID BASIC: restricted to built in situations under normal conditions
- Climatic suitability CSLS and HID Heavy Duty: use in luminaires under humid conditions (not drip-proof)



# Gear for SDW-T lamps

## Versions



BSL 100 K202-A2-TS 230 V 50 Hz

## Dimensional drawing



### Product

CSLS 100 SDW-T 220-240V 50/60Hz

### Product

Product	A1	A2	B1	C1	D1
BSL 100 K202-A2-TS 230V 50Hz	123 mm	98 mm	61 mm	52 mm	6.2 mm

### General Information

Number Of Lamps	1 piece/unit
Lamp Type	SDW-T

## Operating and Electrical

Order Code	Full Product Name	Input Frequency	Input Voltage
90870430	CSLS 100 SDW-T 220-240V 50/60Hz	50 to 60 Hz	220 to 240 V

Order Code	Full Product Name	Input Frequency	Input Voltage
74076700	BSL 100 K202-A2-TS 230V 50Hz	50 Hz	230 V

## System characteristics

## Gear for SDW-T lamps

Order Code	Full Product Name	Rated Ballast-Lamp Power
90870430	CSLS 100 SDW-T 220-240V 50/60Hz	100 W

Order Code	Full Product Name	Rated Ballast-Lamp Power
74076700	BSL 100 K202-A2-TS 230V 50Hz	150/100 W

