



HID ignitors for series systems

SND 57 220-240V 50/60HZ

HID ignitors for series systems

Product data

General Information	
Application code	57
Lamp type	SON
Number of lamps	1 piece/unit
Operating and Electrical	
Input Voltage	220 to 240 V
Input frequency	50 to 60 Hz
Ignition type	Semi-Parallel
Ignition attempts	3
Ignition time (max.)	1185 s
Ignition voltage (max.)	2.5 kV
Ignition voltage (min.)	1.8 kV
Response voltage	195 V
Mains voltage performance (AC)	-8% - +6%
Mains voltage safety (AC)	-10% - +10%
Power losses (nom.)	1.0 W
Wiring	
Ballast contact wire cross section	0.70-2.50 mm ²
Connector type	Screw
System characteristics	
Rated ballast-lamp power	50/70 W

Temperature	
T-ambient (max.)	85 °C
T-ambient (min.)	-20 °C
T-Case maximum (max.)	90 °C


Mechanical and Housing	
Housing	SNI-85

Approval and Application	
Approval marks	CE marking ENEC certificate

Product Data	
Full product code	871150093066830
Order product name	SND 57 220-240V 50/60Hz
EAN/UPC – product	8711500930668
Order code	93066830
Numerator – quantity per pack	1
SAP numerator – packs per outer box	48
Material no. (12 NC)	913700184966
Net Weight (Piece)	0.050 kg

HID ignitors for series systems

Dimensional drawing



Product	D1	C1	A1	A2	B1
SND 57 220-240V 50/60Hz	4.3 mm	38.5 mm	84.5 mm	65.0 mm	41.5 mm

SND 57 220-240V 50/60Hz

