



Electronic ignitor for HID lamp circuits

SN 56

HID ignitors for semi-parallel systems


Product data

General Information	
Application code	56
Operating and Electrical	
Input Voltage	220 to 240 V
Input frequency	50 to 60 Hz
Ignition type	Semi-Parallel
Ignition voltage (max.)	5.0 kV
Ignition voltage (min.)	2.8 kV
Response voltage	196 V
Mains voltage performance (AC)	-8% - +6%
Mains voltage safety (AC)	-10% - +10%
Power losses (nom.)	1.5 W
Wiring	
Ballast contact wire cross section	0.50-2.50 mm ²
Connector type	Screw
Temperature	
T-ambient (max.)	55 °C

T-ambient (min.)	-20 °C
T-Case maximum (max.)	60 °C
Mechanical and Housing	
Housing	Akulon S223
Approval and Application	
Approval marks	CE marking
Product Data	
Full product code	697013372885700
Order product name	SN 56
EAN/UPC – product	6970133728857
Order code	72885700
Numerator – quantity per pack	1
SAP numerator – packs per outer box	20
Material no. (12 NC)	913710010713
SAP net weight (piece)	0.079 kg

Electronic ignitor for HID lamp circuits

Dimensional drawing



Product

SN 56

SN 56

