

MasterConnect LEDtube EM/Mains T8

MASTERConnect LEDtube IA 1200mm UO 16.5W865 T8

Philips MasterConnect LEDtube EM/Mains T8 makes it easy to upgrade to a connected lighting system. Its 2.4 GHz mesh networking technology enables wireless integration with a variety of control devices, such as sensors and switches. The result? Even more energy saving and enhanced flexibility in your space. Through dimming, occupancy sensing and/or daylight harvesting, lamps deliver 50% or more energy saving thanks to MasterConnect technology.

Product data

General Information	
Cap base	G13 [Medium Bi-Pin Fluorescent]
EU RoHS compliant	Yes
Nominal lifetime (nom.)	50000 h
Switching cycle	200,000X
Light Technical	
Colour Code	865 [CCT of 6,500 K]
Beam Angle (Nom)	160 °
Luminous flux (nom.)	2500 lm
Colour designation	Cool Daylight
Correlated Colour Temperature (Nom)	6500 K
Luminous efficacy (rated) (nom.)	151.52 lm/W
Colour consistency	<6
Colour rendering index (nom.)	83
LLMF at end of nominal lifetime (nom.)	70 %

Operating and Electrical	
Input frequency	50 to 60 Hz
Power (Rated) (Nom)	16.5 W
Lamp current (max.)	76 mA
Lamp current (min.)	69 mA
Starting time (nom.)	0.5 s
Warm-up time to 60% light (nom.)	0.5 s
Power factor (nom.)	0.9
Voltage (Nom)	220-240 V
Temperature	
T-ambient (max.)	45 °C
T-ambient (min.)	-20 °C
T storage (max.)	65 °C
T storage (min.)	-40 °C
T-Case maximum (nom.)	45 °C

MasterConnect LEDtube EM/Mains T8

Controls and Dimming

Dimmable Wireless Dim

Mechanical and Housing

Product length 1200 mm

Approval and Application

Energy efficiency label (EEL) A++

Energy-saving product Yes


Approval marks CE marking RoHS compliance KEMA Keur certificate

Energy consumption kWh/1,000 hours 17 kWh

Product Data

Full product code	871869677346800
Order product name	MASTERConnect LEDtube IA 1200mm UO 16.5W865 T8
EAN/UPC – product	8718696773468
Order code	77346800
Numerator – quantity per pack	1
Numerator – packs per outer box	10
SAP material	929001813902
SAP net weight (piece)	0.251 kg


Dimensional drawing



TLED 1200mm 16.5W 2500lm 6500K G13 D


Product	D1	D2	A1	A2	A3
MASTERConnect LEDtube	25.7	28 mm	1199.4	1205.3	1212.4
IA 1200mm UO 16.5W865 T8	mm		mm	mm	mm

Photometric data



Celux Prosimera 4.5 Philips Lighting B.V. Page 1/7


16-5W G13 865 6500K



16-5W G13 830 3000K

MasterConnect LEDtube EM/Mains T8

Photometric data




16-5W G13

Lifetime




16-5W G13



16-5W G13




16-5W G13



16-5W G13

MasterConnect LEDtube EM/Mains T8

Lifetime



16-5W G13

